

CIRCULATION | FILTRATION | HEATING | WATERREATMENT

Poolican combines the three elements essential to clean and healthy water: a circulation pump, an effective cartridge filter, and a salt electrolyser for natural disinfection. And Poolex goes even further by integrating a 4th element essential to your comfort: a Full Inverter heat pump guaranteeing a water temperature always perfect for your bathing.

- Simplified maintenance: Automatic water circulation control.
- Crystal clear water: High performance cartridge filtration system.
- A healthy & balanced water: Automatic salt electrolysis treatment.
- Gideal temperature all year round: Full Inverter heat pump.
- **⇔** Lighting control **NEW**













THE TECHNICAL ROOM 2.0

You are overwhelmed by all the equipment needed to keep your pool spotless and functional? Poolex has the solution for you with the Poolican, an intuitive device that completely simplifies the management of your pool. Compact and easy to install, Poolican fits perfectly near your pool and simply connects to a standard power outlet. Once in service, it allows complete and optimized remote management via the Poolex application.

You control in real time **the water circulation, filtration, disinfection, heating and lighting of the pool,** all from your smartphone, with greater precision. The Poolican streamlines your pool management by centralizing all essential functions, offering an all-in-one solution for maximum performance and a simplified maintenance.

TECHNICAL CHARACTERISTICS

GENERAL		
Pool volume	25 m³	
Power supply	230V - 50 Hz	
Max power.	1,25 kW	
Connections	32 / 38 mm	
Dimensions	805 x 405 x 595 mm	
Noise level at10m	≤ 28 dB	
LED light	12 vdc / 60 W	
Warranty	2 years	
FILTRATION		
Filter D127 x H235 anti-bacterial		
Pureflow as an option		

HEAT PUMP 5KW		
Air 26°C / Water 26°C	Capacity	5kW
	Power consump- tion	0,91 kW
	СОР	5,5
Temperature range		15 / 40°C
Operating range		-7 / 43°C
Refrigerant		R32
Type of compressor		Rotary
Functions		Heating / Cooling/ Auto

SALT CHLORINATOR		
Salinity	3,5 g/l	
Production rate max.	5 g/l	
Cell cleaning	Reverse polarity	
Operating modes	2 modes : normal / boost	
CIRCULATION		
Flow	5.5 m³/h	
Power	140 W	

























Accessories included



