

FOR POOLS
up to **110m³**

EFFICIENCY
Amazing prize!

7 versions
available

SILVERLINE



SILVERLINE

Efficiency at an amazing prize!

- High performance compressor
- Ultra silent & economical
- Anti-corrosion / Anti-UV Metal casing
- Twisted Tech Titanium heat exchanger

**HEAT PUMP WARRANTY
SERVICES AND PARTS**

**2
ANS**

COMPRESSEUR GARANTI

**5
ANS**

**SERPENTIN EN TITANE
GARANTI CONTRE LA CORROSION**

**15
ANS**

	55	70	90	120	150	180	220
Swimming pool volume	20-30m ³	30-40m ³	40-50m ³	45-65m ³	65-75m ³	70-90m ³	80-110m ³
COP air 26°C /water 26°C	6.13	6.21	6.17	6.22	6.20	6.20	6.19
Noise level at 10 m (db(a))	<30	<36	<37	<38	<39	<40	<40



POOLEX SILVERLINE		55	70	90	120	150	180	220
Swimming pool volume		20-30m ³	30-40m ³	40-50m ³	45-65m ³	65-75m ³	70-90m ³	80-110m ³
Reference		PC-SLP055	PC-SLP070	PC-SLP090	PC-SLP120	PC-SLP150	PC-SILVERPRO-180	PC-SILVERPRO-220
Air 26°C Water 26°C Hygro 80%	Capacity (kW)	5.39	7.02	9.31	12.5	15.24	17.92	21.72
	Power consumption (kW)	0.88	1.13	1.51	2.01	2.46	2.89	3.51
	COP	6.13	6.21	6.17	6.22	6.2	6.2	6.19
Air 15°C Water 26°C Hygro 70%	Capacity (kW)	3.9	5.07	7.05	9.05	10.59	12.6	15.3
	Power consumption (kW)	0.81	1.01	1.39	1.78	2.07	2.47	2.98
	COP	4.84	5.02	5.07	5.08	5.12	5.1	5.13
Electricity supply		Mono 230V / 50Hz						
Max Power (kW)		1.29	1.83	2.51	3.03	3.58	4.43	5.46
Max Current (A)		6.26	8.85	11.52	14.5	16.41	19.65	24.22
Heating temperature range		15°C / 40°C						
Operating range		5°C / 43°C						
Flow (m ³ /h)		1.86	2.5	3.2	4.01	4.7	5.6	7
Refrigerant		R32					R410A	
Packaging dimensions (mm)		845x330x610	905x350x645	1005x350x750				1150x425x820
Dimensions (mm)		765x310x490	827x340x531	927x340x636				1067x405x692
Net / Gross weight (kg)		39 / 44	41 / 50	49 / 59	42 / 62	54 / 64	62 / 72	62 / 72
Noise level at 1 m (dB(A))		<46	<46	<47	<48	<49	<51	<51
Noise level at 4 m (dB(A))		<39	<40	<42	<43	<45	<46	<46
Noise level at 10 m (dB(A))		<30	<36	<37	<38	<39	<40	<40
Compressor type		Rotary						
Compressor brand		Toshiba						
Heat exchanger		Twisted Tech® Titanium						
Function		Heating						
Load losses (mCE)		0.9	0.9	1	1.10	1.13	1.15	nc

EU STANDARD
TUV CERTIFIED
Data provided for information purposes only. Can be subject to change without notice.

Poollex Silverline: The best compromise between efficiency and prize.

A high-performance Mitsubishi compressor and a new titanium double-spiral heat-exchanger give it a COP above 6, based on 26/26 conditions*.

Simple to use, the Poollex Silverline has an LCD control panel that can be remotely positioned at up to 10m and includes Touch & Go technology.

Available in 7 output ratings from 5.5 to 22 kW, it is suitable for pools up to 110 m³.

Poollex performance at the lowest price.

The POOLEX + : all accessories included



Delivered on wooden pallet



Anti-vibration support kit



Ø 50mm 1 1/2
Connectors
PVC



Wired control
extension
(10m)



Condensation
drainage pipe



Maintenance kit
Including multi-language
user manual