



NEW

Product Information

- Polyester reinforced filter of two parts, executed in modern white color.
- Maximum working pressure 2.5 bar.
- Supplied with manual 6-way valve (praher). Including vent inside the filter to vent the filter pipes.
- Testing pressure 3.75 bar.
- Folding diffuser to facilitate the loading of media and acces to interior parts.

Filters

+ 5 Years Tank Warranty

F Top Mount with Multiport Valve

1564254040	PPG Filter Top 400
1564254051	PPG Filter Top 510
1564254062	PPG Filter Top 620
1564254068	PPG Filter Top 680
1564254075	PPG Filter Top 750
1564254091	PPG Filter Top 900

	400	510	620	680	750	900
Filter capacity in m³/h at						
- 50 m ³ /h/m ² (backwash capacity)	6.5	10	15	18	22	32
- 30 m ³ /h/m ²	3.9	6	9	10.8	13.2	19.2
Filter Specifications						
- connection dimension in F"	1½"	1½"	1½"	2"	2"	2"
- filter area in m ²	0.13	0.2	0.3	0.36	0.44	0.64
- height in mm	775	1000	1070	1175	1280	1280
- diameter in mm	400	510	620	680	750	900
- weight in kg	12.5	18.5	23.5	27.5	33.5	42.5
- sand kg	50	100	150	175	225	350
- gravel kg	40	80	120	140	180	280